

Lignite Reserves

Red Butte NW Quadrangle, North Dakota

Edward C. Murphy
2007

UNIT DESCRIPTIONS

- Geology Undifferentiated
- Areas of Mined Coal
- 1

Economic Coal Deposits

Economic coal deposits are those that meet the minimum criteria established by coal companies operating surface mines in North Dakota. These economic criteria include a minimum cumulative coal thickness of ten feet-typically occurring in less than two beds, a minimum individual bed thickness of at least 2.5 feet, a ratio of overburden to coal thickness of not more than 10:1, a minimum of 25 feet of overburden, and a maximum depth to coal of approximately 150 feet.

Geologic Symbols

- Extent of Local Lignite Reserves
- Data Points
- RB78-21




Drill Hole Numbers
- Thickness (in feet) of Mineable Lignite
- 26

Thickness in () signifies two beds of coal.

Coal thicknesses were determined by interpretation of electric logs from individual drill holes. Gamma and density logs were typically available for coal exploration holes but, oil wells were often limited to a gamma log run through surface casing.

Other Features

- Unpaved Road



Red Butte NW Quadrangle, North Dakota

Scale 1:24,000

00.51

Miles

Lambert Conformal Conic Projection Standard Parallels 47° 07' 30" and 47° 15' 00"
1927 North American Datum NGVD 1929
USGS 7.5 Minute Topographic Map Contour Interval 10 Feet
Road Layer Rectified to 2003 NAIP Digital Orthophoto

12°

MN

1980 Magnetic North
Declination at Center of Sheet

This project was supported by, in part by the U.S. Geological Survey, Department of Interior, under assistance awards 02ERTAG0016 and 05ERAG0053.