

Field Screening for Shallow Gas in Ward County, North Dakota



Fred J. Anderson 2007

The investigation of shallow natural gas occurrences within existing ground-water observation wells in Burleigh County, North Dakota was conducted over a four day period from July 23 to 26, 2007. A total of 152 observation well sites, consisting of historic and existing ground-water observation wells, drilled in the county for the purposes of ground-water monitoring of unconsolidated and shallow bedrock aquifers, were reviewed prior to the field component of this investigation.

151 of these observation well sites were selected to be visited in the field to (1) determine the actual existence of the well, (2) to verify its location, and (3) perform flame-ionization detector field screening for possible shallow natural gas occurrences. 72 observation well sites were not found during the investigation, suggesting that these wells have either been abandoned or destroyed. 79 observation well site locations were verified to have a ground-water observation well at their prescribed point and were subsequently field screened.

Each of the wells were field screened for the presence of combustible gasses using a portable FID calibrated to methane (101 ppm low-span or 10,000 ppm high-span) in air. The FID was used solely for field screening on all wells. Instrument response was collected at the top of well casing (TOC) and just above the groundwater/air interface (GWI), after the collection of a water level reading within the well using an electric well tape.

Of the existing wells field screened, 27 returned positive FID responses, ranging from 0.2 to >50,000 ppm (5%) as methane; 52 of the wells showed no response (i.e., a 0.0 ppm as methane instrument reading) during field screening at both the TOC and GWI. Four wells were found to have a detectable concentration of methane at the TOC: Well 154-82-32DC5 had an FID response of 7.5 ppm, well 154-82-30CA2 had an FID response of 1.7 ppm, well 155-83-13-CBDC had an FID response of 1.4 ppm, and well 154-82-03BCC returned a trace reading at 0.1 ppm. It has been observed that it is more likely to detect methane at the GWI or higher up in the air column within a given well. It has been less typical to detect methane emanating from the TOC.

The occurrence of FID responses are concentrated within wells that are located within the Souris River valley in the vicinity of the Minot area. Stock wells and individual private, irrigation, or municipal water supply wells were not considered as a part of this investigation.

FID field screening is not a stand-alone analytical tool. It must be used in conjunction with additional analytical methods and procedures. A positive FID instrument response indicates that the presence of methane is highly likely at the well since the instrument is selectively sensitive to methane and is calibrated specifically to a predetermined concentration of methane in air. However, excessive moisture and low oxygen levels or high values of carbon dioxide can influence FID response. A confirmatory gas analysis is required to determine and quantify the absolute presence and concentration of methane and other hydrocarbons that may be present in conjunction with FID field screening results.

The reconnaissance level field screening results presented here are intended to aid in the selection of future candidate observation well locations and or areas to conduct additional sampling and analysis and potentially focus future field investigative efforts.







Figure 1. Graph depicting the relative relationship and maximum values of FID instrument responses from selected wells in Ward County. FID results for each well are presented in order of sampling occurrence from top to bottom. Values shown are those reported from the groundwater/air interface (as CH₄ in ppm). The typical concentration of methane in commercial natural gas is highlighted by the vertical green line at 70%.

Explanation

- Geologic Symbols**
- Existing observation well with a positive numerical FID instrument response in parts per million (ppm) as methane, at the top of casing (TOC/GWI).
 - Existing observation well, no FID response at TOC and/or the GWI.
 - Historical observation well location. No existing well at well site location visited. Well presumed abandoned or destroyed.
 - Nested wells; locations not separable at this scale.
 - (2) Indicates number of wells drilled at same coordinates.
- Other Features**
- Water
 - Water - Intermittent
 - Marsh
 - Section Corners
 - River/Stream - Perennial
 - Stream - Intermittent
 - Federal Highway
 - State Highway
 - Paved Road
 - Unpaved Road



Ward County, North Dakota

