Field Screening for Shallow Gas in Foster County, North Dakota

Fred J. Anderson and Cassie B. Gudmunsen

2010



collected at the top of well casing (TOC) and just above the groundwater/air interface (GWI). After field screening a water level reading within the well was collected using an electric well tape. Of the 69 existing wells field screened, 10 returned positive FID responses ranging from 0.1 to 185.6 ppm as methane (Figure 1); 59 of the wells showed no response (i.e., a 0.0 ppm as methane instrument reading) during field screening at both the TOC and GWI. It has been observed in the field that it is more likely to detect methane at the GWI or higher up in the air column within a given well. It has been less typical to actually detect methane emanating from the TOC. The occurrences of FID responses are located in the northwestern and eastern parts of the county, coincident with the Carrington, Eastman, and New Rockford Aquifers. Individual private, irrigation, or municipal water supply wells were not considered as a part of this investigation.

FID field screening is not a stand-alone analytical tool. It must be used in conjunction with additional analytical methods and procedures. A positive FID instrument response indicates that the presence of methane is highly likely at the well since the instrument is selectively sensitive to methane and is calibrated specifically to a predetermined concentration of methane in air. However, excessive moisture and low oxygen levels or high values of carbon dioxide can influence FID response. A confirmatory gas analysis is required to determine and quantify the absolute presence and concentration of methane and other hydrocarbons that may be present in conjunction with FID screening results. The reconnaissance level screening results presented here are intended to aid in the selection of future candidate observation well locations and or areas to conduct additional sampling and analysis and potentially focus future field investigative and exploration efforts.









Figure 1. Graph depicting the relative relationship and absolute maximum values of flame-ionization detector (FID) instrument responses from selected wells in Foster County. FID results for each well are presented in order of field screening occurrence from top to bottom. Values shown are those reported from the ground-water/ air interface (GWI) (as CH4 in ppm). The concentration of methane typical in commercial natural gas is highlighted by the vertical green line at 70%.



Historical observation well location. No existing well at well site location visited. Well presumed abandoned or destroyed. Wells sites not visited during this investigation. Nested wells; locations not separable at this scale. Indicates number of wells drilled at same coordinates.

Other Features

0

(2)

Water	281	US Highway
Water - Intermittent	20	State Highway
Marsh		Paved Road
 River/Stream - Perennial		Unpaved Road
 Stream - Intermittent		



