

BEFORE THE INDUSTRIAL COMMISSION
OF THE STATE OF NORTH DAKOTA

CASE NO. 15869
ORDER NO. 18123

IN THE MATTER OF A HEARING CALLED ON
A MOTION OF THE COMMISSION TO
CONSIDER THE ON A MOTION OF THE
COMMISSION TO CONSIDER ADOPTING NEW
RULES AND AMENDMENTS TO THE
"GENERAL RULES AND REGULATIONS FOR
THE CONSERVATION OF CRUDE OIL AND
NATURAL GAS" CODIFIED AS ARTICLE 43-02
NORTH DAKOTA ADMINISTRATIVE CODE.

ORDER OF THE COMMISSION

THE COMMISSION FINDS:

- (1) This cause came on for hearing at 9:00 a.m. on the 1st day of November, 2011.
- (2) The record of this case was open for thirteen (13) days after the hearing to receive written comments on the proposed additions and amendments to the rules. The record closed November 14, 2011.
- (3) The Commission is authorized to adopt, and from time to time amend or repeal, reasonable rules in conformity with the provisions of any statute administered or enforced by the agency.
- (4) It is necessary to adopt new rules and amend existing rules codified in North Dakota Administrative Code (NDAC) Chapters 43-02-03 and 43-02-12 to implement, administer, and enforce the provisions of North Dakota Century Code Chapters 38-08 and 38-08.1.
- (5) The amendment of existing rules are in the public interest.

IT IS THEREFORE ORDERED:

- (1) New and amended sections to NDAC Chapters 43-02-03 and 43-02-12 as shown in the appendix to this order, are hereby approved and adopted.
- (2) Existing regulations not specifically amended by this order shall remain in full force and effect.

(3) This order shall be effective pursuant to the applicable statutes and laws of this state and shall remain in full force and effect until further order of the Commission.

Dated this 23rd day of January, 2012.

INDUSTRIAL COMMISSION
STATE OF NORTH DAKOTA

By the Director, on behalf of the Commission

/s/ Lynn D. Helms, Director

APPENDIX TO COMMISSION ORDER NO. 18123

NORTH DAKOTA INDUSTRIAL COMMISSION

RULES AND REGULATIONS—NORTH DAKOTA ADMINISTRATIVE CODE

2012 RULE CHANGES

RULES AND REGULATIONS

NORTH DAKOTA ADMINISTRATIVE CODE

CHAPTER 43-02-03 (OIL & GAS)

CHAPTER 43-02-12 (GEOPHYSICAL EXPLORATION)

GENERAL RULES AND REGULATIONS

CHAPTER 43-02-03

43-02-03-05. ENFORCEMENT OF LAWS, RULES, AND REGULATIONS DEALING WITH CONSERVATION OF OIL AND GAS. The commission, its agents, representatives, and employees are charged with the duty and obligation of enforcing all rules and statutes of North Dakota relating to the conservation of oil and gas. However, it shall be the responsibility of all the owners or operators to obtain information pertaining to the regulation of oil and gas before operations have begun.

~~The director may shut in, for no more than forty days, any well that is likely to cause a serious threat of pollution or injury to the public health or safety.~~

History: Amended effective May 1, 2004.

General Authority
NDCC 38-08-04

Law Implemented
NDCC 38-08-04

43-02-03-15. BOND AND TRANSFER OF WELLS.

1. Bond requirements. Prior to commencing drilling operations, any person who proposes to drill a well for oil, gas, or injection shall submit to the commission, and obtain its approval, a surety bond or cash bond. An alternative form of security may be approved by the commission after notice and hearing, as provided by law. The operator of such well shall be the principal on the bond covering the well. Each surety bond shall be executed by a responsible surety company authorized to transact business in North Dakota.

2. Bond amounts and limitations. The bond shall be in the amount of ~~twenty~~ fifty thousand dollars when applicable to one well only. Wells drilled to a total depth of less than two thousand feet [609.6 meters] may be bonded in a lesser amount if approved by the director. When the principal on the bond is drilling or operating a number of wells within the state or proposes to do so, the principal may submit a bond conditioned as provided by law. Wells utilized for commercial disposal operations must be bonded in the amount of fifty thousand dollars. ~~A blanket bond covering ten wells or less shall be in the amount of fifty thousand dollars provided the bond shall be limited to no more than three of the following in aggregate and a blanket bond covering more than ten~~ one wells well shall be in the amount of one hundred thousand dollars, provided the bond shall be limited to no more than six of the following in aggregate:
- a. A well that is a dry hole and is not properly plugged;
 - b. A well that is plugged and the site is not properly reclaimed; and
 - c. A well that is abandoned pursuant to section 43-02-03-55 and is not properly plugged and the site is not properly reclaimed.

If this aggregate of wells is reached, all well permits, for which drilling has not commenced, held by the principal of such bond are suspended. No rights may be exercised under the permits until the aggregate of wells drops below the required limit, or the operator files the appropriate bond to cover the permits, at which time the rights given by the drilling permits are reinstated. A well with an approved temporary abandoned status shall have the same status as an oil, gas, or injection well. The commission may, after notice and hearing, require higher bond amounts than those referred to in this section. Such additional amounts for bonds must be related to the economic value of the well or wells and the expected cost of plugging and well site reclamation, as determined by the commission. The commission may refuse to accept a bond or to add wells to a blanket bond if the operator or surety company has failed in the past to comply with statutes, rules, or orders relating to the operation of wells; if a civil or administrative action brought by the commission is pending against the operator or surety company; or for other good cause.

3. Unit bond requirements. Prior to commencing unit operations, the operator of any area under unitized management shall submit to the commission, and obtain its approval, a surety bond or cash bond. An alternative form of security may be approved by the commission after notice and hearing, as provided by law. The operator of the unit shall be the principal on the bond covering the unit. The amount of the bond shall be specified by the commission in the order approving the plan of unitization. Each surety bond shall be executed by a responsible surety company authorized to transact business in North Dakota.

Prior to transfer of a unit to a new operator, the commission, after notice and hearing, may revise the bond amount for a unit, or in the case when the unit was not previously bonded, the commission may require a bond and set a bond amount for the unit.

4. Bond terms. Bonds shall be conditioned upon full compliance with North Dakota Century Code chapter 38-08, and all administrative rules and orders of the commission. It shall be a plugging bond, as well as a drilling bond, and is to endure up to and including approved plugging of all oil, gas, and injection wells as well as dry holes. Approved plugging shall also include practical reclamation of the well site and appurtenances thereto. If the principal does not satisfy the bond's conditions, then the surety shall satisfy the conditions or forfeit to the commission the face value of the bond.
5. Transfer of wells under bond. Transfer of property does not release the bond. In case of transfer of property or other interest in the well and the principal desires to be released from the bond covering the well, such as producers, not ready for plugging, the principal must proceed as follows:
 - a. The principal must notify the director, in writing, of all proposed transfers of wells at least thirty days before the closing date of the transfer. The director may, for good cause, waive this requirement.

The principal shall submit to the commission a form 15 reciting that a certain well, or wells, describing each well by quarter-quarter, section, township, and range, is to be transferred to a certain transferee, naming such transferee, for the purpose of ownership or operation. The date of assignment or transfer must be stated and the form signed by a party duly authorized to sign on behalf of the principal.

On said transfer form the transferee shall recite the following: "The transferee has read the foregoing statement and does accept such transfer and does accept the responsibility of such well under the transferee's one-well bond or, as the case may be, does accept the responsibility of such wells under the transferee's blanket bond, said bond being tendered to or on file with the commission." Such acceptance must likewise be signed by a party authorized to sign on behalf of the transferee and the transferee's surety.

- b. When the commission has passed upon the transfer and acceptance and accepted it under the transferee's bond, the transferor shall be released from the responsibility of plugging the well and site reclamation. If such wells include all the wells within the responsibility of the transferor's bond, such bond will be released by the commission upon written request. Such request must be signed by an officer of the transferor or a person authorized to sign for the transferor. The director may refuse to transfer any well from a bond if the well is in violation of a statute, rule, or order.
 - c. The transferee (new operator) of any oil, gas, or injection well, shall be responsible for the plugging and site reclamation of any such well. For that purpose the transferee shall submit a new bond or, in the case of a surety bond, produce the written consent of the surety of the original or prior bond that the latter's responsibility shall continue and attach to such well. The original or prior bond shall not be released as to the plugging and reclamation responsibility of any such transferor until the transferee shall submit to the commission an acceptable bond to cover such well. All liability on bonds shall continue until the plugging and site reclamation of such wells is completed and approved.

6. Treating plant bond. Prior to the commencement of operations, any person proposing to operate a treating plant must submit to the commission and obtain its approval of a surety bond or cash bond. An alternative form of security may be approved by the commission after notice and hearing, as provided by law. The person responsible for the operation of the plant shall be the principal on the bond. Each surety bond shall be executed by a responsible surety company authorized to transact business in North Dakota. The amount of the bond must be as prescribed in section 43-02-03-51. It is to remain in force until the operations cease, all equipment is removed from the site, and the site and appurtenances thereto are reclaimed, or liability of the bond is transferred to another bond that provides the same degree of security. If the principal does not satisfy the bond's conditions, then the surety shall satisfy the conditions or forfeit to the commission the face value of the bond.
7. Bond termination. The commission shall, in writing, advise the principal and any sureties on any bond as to whether the plugging and reclamation is approved. If approved, liability under such bond may be formally terminated upon receipt of a written request by the principal. The request must be signed by an officer of the principal or a person authorized to sign for the principal.
8. Director's authority. The director is vested with the power to act for the commission as to all matters within this section, except requests for alternative forms of security, which may only be approved by the commission.

History: Amended effective April 30, 1981; March 1, 1982; January 1, 1983; May 1, 1990; May 1, 1992; May 1, 1994; December 1, 1996; September 1, 2000; July 1, 2002; May 1, 2004; January 1, 2006.

General Authority
NDCC 38-08-04

Law Implemented
NDCC 38-08-04

43-02-03-16. APPLICATION FOR PERMIT TO DRILL AND RECOMPLETE.

Before any person shall begin any well-site preparation for the drilling of any well other than surveying and staking, such person shall file an application for permit to drill (form 1) with the director, together with a permit fee of one hundred dollars. Verbal approval may be given for site preparation by the director in extenuating circumstances. No drilling activity shall commence until such application is approved and a permit to drill is issued by the director. The application must be accompanied by the bond pursuant to section 43-02-03-15 or the applicant must have previously filed such bond with the commission, otherwise the application is incomplete. An incomplete application received by the commission has no standing and will not be deemed filed until it is completed.

The application for permit to drill shall be accompanied by an accurate plat certified by a registered surveyor showing the location of the proposed well with reference to true north and the nearest lines of a governmental section. The plat shall also include latitude and longitude of the proposed well location to the nearest tenth of a second. Information to be included in such application shall be the proposed depth to which the well will be drilled, estimated depth to the

top of important markers, estimated depth to the top of objective horizons, the proposed mud program, the proposed casing program, including size and weight thereof, the depth at which each casing string is to be set, the proposed pad layout, including cut and fill diagrams, and the proposed amount of cement to be used, including the estimated top of cement.

Prior to the commencement of recompletion operations or drilling horizontally in the existing pool, an application for permit shall be filed with the director. Included in such application shall be the notice of intention (form 4) to reenter a well by drilling horizontally, deepening, or plugging back to any source of supply other than the producing horizon in an existing well. Such notice shall include the name and file number and exact location of the well, the approximate date operations will begin, the proposed procedure, the estimated completed total depth, the anticipated hydrogen sulfide content in produced gas from the proposed source of supply, the weight and grade of all casing currently installed in the well unless waived by the Director, the casing program to be followed, and the original total depth with a permit fee of fifty dollars. The director may deny any application if it is determined, in accordance with the latest version of ANSI/NACE MR0175/ISO 15156, that the casing currently installed in the well would be subject to sulfide stress cracking.

The applicant shall provide all information, in addition to that specifically required by this section, if requested by the director. The director may impose such terms and conditions on the permits issued under this section as the director deems necessary.

The director shall deny an application for a permit under this section if the proposal would cause, or tend to cause, waste or violate correlative rights. The director of oil and gas shall state in writing to the applicant the reason for the denial of the permit. The applicant may appeal the decision of the director to the commission.

A permit to drill automatically expires one year after the date it was issued, unless the well is drilling or has been drilled below surface casing. A permit to recomplete or to drill horizontally automatically expires one year after the date it was issued, unless such project has commenced.

History: Amended effective April 30, 1981; January 1, 1983; May 1, 1992; May 1, 1994; September 1, 2000; July 1, 2002; April 1, 2010.

General Authority
NDCC 38-08-05

Law Implemented
NDCC 38-08-05

43-02-03-16.3. RECOVERY OF A RISK PENALTY. The following govern the recovery of the risk penalty pursuant to subsection 3 of North Dakota Century Code section 38-08-08 and subsection 3 of North Dakota Century Code section 38-08-09.4:

1. An owner may recover the risk penalty under the provisions of subsection 3 of North Dakota Century Code section 38-08-08, provided the owner gives, to the owner from whom the penalty is sought, a written invitation to participate in the risk and cost of drilling a well, including reentering a plugged and abandoned well, or the risk and cost of reentering an existing well to drill deeper or a horizontal lateral. If the nonparticipating owner's interest is not subject to a lease or other contract for

development, an owner seeking to recover a risk penalty must also make a good-faith attempt to have the unleased owner execute a lease.

- a. The invitation to participate in drilling must contain the following:
 - (1) The approximate location of the proposed or existing well and its proposed depth and objective zone.
 - (2) An itemization of the estimated costs of drilling and completion.
 - (3) The approximate date upon which the well was or will be spudded or reentered.
 - (4) A statement indicating the invitation must be accepted within thirty days of receiving it.
 - (5) Notice that the participating owners plan to impose a risk penalty and that the nonparticipating owner may object to the risk penalty by either responding in opposition to the petition for a risk penalty, or if no such petition has been filed, by filing an application or request for hearing with the commission.
 - (6) Drilling or spacing unit description.
 - b. An election to participate must be in writing and must be received by the owner giving the invitation within thirty days of the participating party's receipt of the invitation.
 - c. An invitation to participate and an election to participate must be served personally, by mail requiring a signed receipt, or by overnight courier or delivery service requiring a signed receipt. Failure to accept mail requiring a signed receipt constitutes service.
 - d. An election to participate is only binding upon an owner electing to participate if the well is spudded or reentry operations are commenced on or before ninety days after the date the owner extending the invitation to participate sets as the date upon which a response to the invitation is to be received. It also expires if the permit to drill or reenter expires without having been exercised. If an election to participate lapses, a risk penalty can only be collected if the owner seeking it again complies with the provisions of this section.
2. An owner may recover the risk penalty under the provisions of subsection 3 of North Dakota Century Code section 38-08-09.4, provided the owner gives, to the owner from whom the penalty is sought, a written invitation to participate in the unit expense. If the nonparticipating owner's interest is not subject to a lease or other contract for development, an owner seeking to recover a risk penalty must also make a good-faith attempt to have the unleased owner execute a lease.

- a. The invitation to participate in the unit expense must contain the following:
 - (1) A description of the proposed unit expense, including the location, objectives, and plan of operation.
 - (2) An itemization of the estimated costs.
 - (3) The approximate date upon which the proposal was or will be commenced.
 - (4) A statement indicating the invitation must be accepted within thirty days of receiving it.
 - (5) Notice that the participating owners plan to impose a risk penalty and that the nonparticipating owner may object to the risk penalty by either responding in opposition to the petition for a risk penalty, or if no such petition has been filed, by filing an application or request for hearing with the commission.
 - b. An election to participate must be in writing and must be received by the owner giving the invitation within thirty days of the participating party's receipt of the invitation.
 - c. An invitation to participate and an election to participate must be served personally, by mail requiring a signed receipt, or by overnight courier or delivery service requiring a signed receipt. Failure to accept mail requiring a signed receipt constitutes service.
 - d. An election to participate is only binding upon an owner electing to participate if the unit expense is commenced within ninety days after the date the owner extending the invitation request to participate sets as the date upon which a response to the request invitation is to be received. If an election to participate lapses, a risk penalty can only be collected if the owner seeking it again complies with the provisions of this section.
 - e. An invitation to participate in a unit expense covering monthly operating expenses shall be effective for all such monthly operating expenses for a period of five years if the unit expense identified in the invitation to participate is first commenced within ninety days after the date set in the invitation to participate as the date upon which a response to the invitation to participate must be received. An election to participate in a unit expense covering monthly operating expenses is effective for five years after operations are first commenced. If an election to participate in a unit expense comprised of monthly operating expenses expires or lapses after five years, a risk penalty may only be assessed and collected if the owner seeking the penalty once again complies with this section.
3. Upon its own motion or the request of a party, the commission may include in a pooling order requirements relating to the invitation and election to participate, in

which case the pooling order will control to the extent it is inconsistent with this section.

History: Effective December 1, 1996; amended effective May 1, 2004; January 1, 2006; January 1, 2008; April 1, 2010.

General Authority
NDCC 38-08-04

Law Implemented
NDCC 38-08-04
38-08-08

43-02-03-18. DRILLING UNITS - WELL LOCATIONS. In the absence of an order by the commission setting spacing units for a pool:

1. a. Vertical or directional oil wells projected to a depth not deeper than the Mission Canyon formation must be drilled upon a governmental quarter-quarter section or equivalent lot, located not less than five hundred feet [152.4 meters] to the boundary of such governmental quarter-quarter section or equivalent lot. No more than one well shall be drilled to the same pool on any such governmental quarter-quarter section or equivalent lot, except by order of the commission, nor shall any well be drilled on any such governmental quarter-quarter section or equivalent lot containing less than thirty-six acres [14.57 hectares] except by order of the commission.
- b. Vertical or directional oil wells projected to a depth deeper than the Mission Canyon formation must be drilled on a governmental quarter section or equivalent lots, located not less than six hundred sixty feet [201.17 meters] to the boundary of such governmental quarter section or equivalent lots. No more than one well shall be drilled to the same pool on any such governmental quarter section or equivalent lots, except by order of the commission, nor shall any well be drilled on any such governmental quarter section or equivalent lots containing less than one hundred forty-five acres [58.68 hectares] except by order of the commission.
2. a. Horizontal wells with a horizontal displacement of the well bore drilled at an angle of at least eighty degrees within the productive formation of at least five hundred feet [152.4 meters], projected to a depth not deeper than the Mission Canyon formation, must be drilled upon a drilling unit described as a governmental section or described as two adjacent governmental quarter sections within the same section or equivalent lots, located not less than five hundred feet [152.4 meters] to the outside boundary of such tract. The horizontal well proposed to be drilled must, in the director's opinion, justify the creation of such drilling unit. No more than one well may be drilled to the same pool on any such tract, except by order of the commission.
- b. Horizontal wells with a horizontal displacement of the well bore drilled at an angle of at least eighty degrees within the productive formation of at least five hundred feet [152.4 meters], projected to a depth deeper than the Mission

Canyon formation, must be drilled upon a drilling unit described as a governmental section, located not less than five hundred feet [152.4 meters] to the outside boundary of such tract. The horizontal well proposed to be drilled must, in the director's opinion, justify the creation of such drilling unit. No more than one well may be drilled to the same pool on any such tract, except by order of the commission.

3. a. Gas wells projected to a depth not deeper than the Mission Canyon formation shall be drilled upon a governmental quarter section or equivalent lots, located not less than five hundred feet [152.4 meters] to the boundary of such governmental quarter section or equivalent lots. No more than one well shall be drilled to the same pool on any such governmental quarter section or equivalent lots, except by order of the commission, nor shall any well be drilled on any such governmental quarter section or equivalent lot containing less than one hundred forty-five acres [58.68 hectares] except by order of the commission.
 - b. Gas wells projected to a depth deeper than the Mission Canyon formation shall be drilled upon a governmental quarter section or equivalent lots, located not less than six hundred sixty feet [201.17 meters] to the boundary of such governmental quarter section or equivalent lots. No more than one well shall be drilled to the same pool on any such governmental quarter section or equivalent lots, except by order of the commission, nor shall any well be drilled on any such governmental quarter section or equivalent lot containing less than one hundred forty-five acres [58.68 hectares] except by order of the commission.
4. Within thirty days, or a reasonable time thereafter, following the discovery of oil or gas in a pool not then covered by an order of the commission, a spacing hearing shall be docketed. Following such hearing the commission shall issue an order prescribing a temporary spacing pattern for the development of the pool. This order shall continue in force for a period of not more than ~~eighteen months~~ three years at the expiration of which time a hearing shall be held at which the commission may require the presentation of such evidence as will enable the commission to determine the proper spacing for the pool.

During the interim period between the discovery and the issuance of the temporary order, no permits shall be issued for the drilling of an offset well to the discovery well, unless approved by the director. Approval shall be consistent with anticipated spacing for the orderly development of the pool.

Any well drilled within one mile [1.61 kilometers] of an established field shall conform to the spacing requirements in that field except when it is apparent that the well will not produce from the same common source of supply. In order to assure uniform and orderly development, any well drilled within one mile [1.61 kilometers] of an established field boundary shall conform to the spacing and special field rules for the field, and for the purposes of spacing and pooling, the field boundary shall be extended to include the spacing unit for such well and any intervening lands. The foregoing shall not be applicable if it is apparent that the well will not produce from the same common source of supply as wells within the field.

5. If the director denies an application for permit, the director shall advise the applicant immediately of the reasons for denial. The decision of the director may be appealed to the commission.

History: Amended effective April 30, 1981; January 1, 1983; May 1, 1992; May 1, 1994; July 1, 1996; July 1, 2002; January 1, 2006; April 1, 2010.

General Authority
NDCC 38-08-04
38-08-07

Law Implemented
NDCC 38-08-04
38-08-07

~~43-02-03-19. RESERVE PIT FOR DRILLING MUD AND DRILL CUTTINGS~~
RECLAMATION OF SURFACE SITE CONSTRUCTION. In the construction of a drill site, access road, and all associated facilities, the topsoil shall be removed, stockpiled, and stabilized or otherwise reserved for use when the area is reclaimed. "Topsoil" means the suitable plant growth material on the surface; however, in no event shall this be deemed to be more than the top eight inches [20.32 centimeters] of soil. Soil stabilization additives and materials to be used on site, access roads or associated facilities must have approval from the director before application.

When necessary to prevent pollution of the land surface and freshwaters, the director may require the drill site to be sloped and diked, ~~to divert surface drainage.~~

~~In order to assure a supply of proper material or mud laden fluid to confine oil, gas, or water to its native strata during the drilling of any well, each operator shall provide, before drilling is commenced, a container or reserve pit of sufficient size to contain said material or fluid, and the accumulation of drill cuttings. A reserve pit may be utilized to contain solids and fluids used and generated during well drilling and completion operations, providing the pit can be constructed, used and reclaimed in a manner that will prevent pollution of the land surface and freshwaters. In special circumstances, the director may prohibit construction of a reserve pit or may impose more stringent pit construction and reclamation requirements. Under no circumstances shall reserve pits be used for disposal, dumping, or storage of fluids, wastes, and debris other than drill cuttings and fluids used or recovered while drilling and completing the well.~~

~~Reserve pits~~ Well sites and associated production facilities shall not be located in, or hazardingly near, bodies of water, nor shall they block natural drainages. ~~No reserve pit shall be wholly or partially constructed in fill dirt unless approved by the director.~~ Sites and associated production facilities shall be designed to divert surface drainage from entering the site.

~~When required by the director, the reserve pit or site~~ Well sites and associated production facilities or appropriate parts thereof ~~must~~ shall be fenced ~~if required by the director.~~

- ~~1. Within a reasonable time, but not more than one year, after the completion of a well, the reserve pit shall be reclaimed. Prior to reclaiming the pit, the operator or the operator's agent shall file a sundry notice (form 4) with the director and obtain~~

~~approval of a pit reclamation plan. Verbal approval to reclaim the pit may be given. The notice shall include, but not be limited to:~~

- ~~a. The name and address of the reclamation contractor;~~
- ~~b. The name and address of the surface owner;~~
- ~~c. The location and name of the disposal site for the pit water; and,~~
- ~~d. A description of the proposed work, including details on treatment and disposition of the drilling waste.~~

~~All pit water and oil on the pit must be removed prior to reclamation. Drilling waste should be encapsulated in the pit and covered with at least four feet [1.22 meters] of backfill and topsoil and surface sloped, when practicable, to promote surface drainage away from the reclaimed pit area.~~

2. ~~Within a reasonable time, but not more than one year, after a well is plugged, the well site, access road, and other associated facilities constructed for the well shall be reclaimed as closely as practicable to original condition, or in the case of a completed well, the unused portion of the site shall be reclaimed. Prior to site reclamation, the operator or the operator's agent shall file a sundry notice (form 4) with the director and obtain approval of a reclamation plan. The operator or operator's agent shall provide a copy of the proposed reclamation plan to the surface owner at least ten days prior to commencing the work unless waived by the surface owner. Verbal approval to reclaim the site may be given. The notice shall include, but not be limited to:~~

- ~~a. The name and address of the reclamation contractor;~~
- ~~b. The name and address of the surface owner and the date when a copy of the proposed reclamation plan was provided to the surface owner;~~
- ~~c. A description of the proposed work, including topsoil redistribution and reclamation plans for the access road and other associated facilities; and~~
- ~~d. Reseeding plans, if applicable.~~

~~The commission will mail a copy of the approved notice to the surface owner.~~

~~All production equipment, waste and debris shall be removed from the site. Flow lines shall be purged in a manner approved by the director. Flow lines shall be removed if buried less than three feet [91.44 centimeters] below final contour.~~

3. ~~Gravel or other surfacing material shall be removed and the well site, access road, and other associated facilities constructed for the well shall be reshaped as near as is practicable to original contour.~~

4. ~~The stockpiled topsoil shall be evenly distributed over the disturbed area, and where applicable the area revegetated with native species or according to the reasonable specifications of the appropriate government land manager or surface owner.~~
5. ~~Within thirty days after completing any reclamation, the operator shall file a sundry notice with the director reporting the work performed.~~
6. ~~The director, with the consent of the appropriate government land manager or surface owner, may waive the requirement of reclamation of the site and access road after a well is plugged.~~

Within six months after the completion of a well, the portion of the well site not used for well operations shall be reclaimed, unless waived by the director. Well sites and all associated facilities shall be stabilized to prevent erosion.

History: Amended effective March 1, 1982; January 1, 1983; May 1, 1992; July 1, 2002; January 1, 2008; April 1, 2010.

General Authority
NDCC 38-08-04

Law Implemented
NDCC 38-08-04

43-02-03-19.1. FENCING, SCREENING, AND NETTING OF DRILLING AND RESERVE PITS. All open pits and ponds which contain saltwater must be fenced. All pits and ponds which contain oil must be fenced, screened, and netted.

This is not to be construed as requiring the fencing, screening, or netting of a ~~reserve~~ drilling pit or ~~other earthen~~ reserve pit used solely for drilling, completing, recompleting, or plugging unless such pit is not reclaimed ~~in excess of~~ within ninety days after completion of ~~the operation~~ drilling operations.

History: Effective May 1, 1992.

General Authority
NDCC 38-08-04

Law Implemented
NDCC 38-08-04

43-02-03-19.2 DISPOSAL OF WASTE MATERIAL. All waste material associated with exploration or production of oil and gas must be properly disposed of in an authorized facility in accord with all applicable local, state, and federal laws and regulations.

All waste material recovered from spills, leaks, and other such events shall immediately be disposed of in an authorized facility, although the remediation of such material may be allowed on-site if approved by the director.

This is not to be construed as requiring the offsite disposal of drilling mud from shallow wells or drill cuttings associated with the drilling of a well. However, ~~top~~ water remaining in ~~the a~~ drilling or reserve pit used in the drilling and completion operations is to be removed from the

~~reserve~~ pit and disposed of in an authorized disposal well or used in a manner approved by the director. The disposition or use of the water must be included on the sundry notice (form 4) reporting the plan of reclamation pursuant to sections 43-02-03-19.4 and 43-02-03-19.5.

History: Effective May 1, 1992; amended effective May 1, 1994; September 1, 2000.

General Authority
NDCC 38-08-04

Law Implemented
NDCC 38-08-04

43-02-03-19.3. EARTHEN PITS AND OPEN RECEPTACLES. Except as otherwise provided in sections 43-02-03-19.4 and 43-02-03-19.5, no saltwater, drilling mud, crude oil, waste oil, or other waste shall be stored in earthen pits or open receptacles except in an emergency and upon approval by the director.

~~An~~ A lined earthen pit or open receptacle may be temporarily used to retain oil, water, cement, solids or fluids generated in well completion, servicing, or plugging operations. A pit or receptacle used for this purpose must be sufficiently impermeable to provide adequate temporary containment of the oil, water, or fluids. The contents of the pit or receptacle must be removed within seventy-two hours after operations have ceased and must be disposed of at an authorized facility in accordance with section 43-02-03-19.2. Within thirty days after operations have ceased, the earthen pit shall be reclaimed and the open receptacle shall be removed. The director may grant an extension of the thirty day time period to no more than one year for good reason.

The director may permit pits or receptacles used solely for the purpose of flaring casinghead gas. A pit or receptacle used for this purpose must be sufficiently impermeable to provide adequate temporary containment of fluids. Permission for such pit or receptacle ~~will~~ shall be conditioned on locating the pit not less than one hundred fifty feet [45.72 meters] from the vicinity of wells and tanks and keeping it free of any saltwater, crude oil, waste oil, or other waste. Saltwater, drilling mud, crude oil, waste oil, or other waste shall be removed from the pit or receptacle within twenty-four hours after being discovered and must be disposed of at an authorized facility in accordance with section 43-02-03-19.2.

The director may permit pits used solely for storage of freshwater used in completion and well servicing operations. Permits for freshwater pits shall be valid for a period of one year but may be re-authorized upon application. Freshwater pits shall be lined and no pit constructed for this purpose shall be wholly or partially constructed in fill dirt unless approved by the director. The director may approve chemical treatment to municipal drinking water standards upon application. The freshwater pit shall have signage on all sides accessible to vehicular traffic clearly identifying the usage as freshwater only.

History: Effective September 1, 2000; April 1, 2010.

General Authority
NDCC 38-08-04

Law Implemented
NDCC 38-08-04

Create a new Section of the Administrative Code:

43-02-03-19.4. DRILLING PITS. A pit may be utilized to bury drill cuttings and solids generated during well drilling and completion operations, providing the pit can be constructed, used and reclaimed in a manner that will prevent pollution of the land surface and freshwaters. In special circumstances, the director may prohibit construction of a cuttings pit or may impose more stringent pit construction and reclamation requirements. Reserve and circulation of mud system through earthen pits are prohibited unless a waiver is granted by the director. All pits shall be inspected by an authorized representative of the director prior to lining and use. Under no circumstances shall pits be used for disposal, dumping, or storage of fluids, wastes, and debris other than drill cuttings and solids recovered while drilling and completing the well.

Drill cuttings and solids must be stabilized in a manner approved by the director prior to placement in a cuttings pit. Any liquid accumulating in the cuttings pit shall be promptly removed. The pit shall be diked in a manner to prevent surface water from running into the pit.

A small lined pit can be authorized by the director for the temporary containment of incidental fluids such as trench water and rig wash, if emptied and covered prior to the rig leaving the site.

Pits shall not be located in, or hazardously near, bodies of water, nor shall they block natural drainages. No pit shall be wholly or partially constructed in fill dirt unless approved by the director.

When required by the director, the drilling pit or appropriate parts thereof shall be fenced.

Within thirty days after the drilling of a well or expiration of a drilling permit, drilling pits shall be reclaimed. The director may grant an extension of the thirty day time period to no more than one year for good reason. Prior to reclaiming the pit, the operator or the operator's agent shall file a sundry notice (form 4) with the director and obtain approval of a pit reclamation plan. Verbal approval to reclaim the pit may be given. The notice shall include, but not be limited to:

1. The name and address of the reclamation contractor;
2. The name and address of the surface owner;
3. The location and name of the disposal site for the pit water when applicable; and,
4. A description of the proposed work, including details on treatment and disposition of the drilling waste.

Any water or oil accumulated on the pit must be removed prior to reclamation. Drilling waste shall be encapsulated in the pit and covered with at least four feet [1.22 meters] of backfill and topsoil and surface sloped, when practicable, to promote surface drainage away from the reclaimed pit area.

History: Effective _____.

General Authority
NDCC 38-08-04

Law Implemented
NDCC 38-08-04

Create a new Section of the Administrative Code:

43-02-03-19.5. RESERVE PIT FOR DRILLING MUD AND DRILL CUTTINGS FROM SHALLOW WELLS. For wells drilled to a strata or formation, including lignite or coal strata or seam, located above the depth of five thousand feet [1524 meters] below the surface, or located more than five thousand feet [1524 meters] below the surface but above the top of the Rierdon formation, a container or reserve pit of sufficient size to contain said material or fluid, and the accumulation of drill cuttings may be utilized to contain solids and fluids used and generated during well drilling and completion operations, providing the pit can be constructed, used and reclaimed in a manner that will prevent pollution of the land surface and freshwaters. A reserve pit may be allowed by an order of the commission after notice and hearing for wells drilled within a specified field and pool more than five thousand feet [1524 meters] below the surface and below the top of the Rierdon formation provided the proposed well or wells utilize a low sodium content water based mud system and the reserve pit can be constructed, used, and reclaimed in a manner that will prevent pollution of the land surface and freshwaters. In special circumstances, based on site specific conditions, the director or authorized representative may prohibit construction of a reserve pit or may impose more stringent pit construction and reclamation requirements, including reserve pits previously authorized by a commission order within a specified field and pool. Under no circumstances shall reserve pits be used for disposal, dumping, or storage of fluids, wastes, and debris other than drill cuttings and fluids used or recovered while drilling and completing the well.

Reserve pits shall not be located in, or hazardously near, bodies of water, nor shall they block natural drainages. No reserve pit shall be wholly or partially constructed in fill dirt unless approved by the director.

1. Within a reasonable time, but not more than one year after the completion of a shallow well, or prior to drilling below the surface casing shoe on any other well, the reserve pit shall be reclaimed. Prior to reclaiming the pit, the operator or the operator's agent shall file a sundry notice (form 4) with the director and obtain approval of a pit reclamation plan. Verbal approval to reclaim the pit may be given. The notice shall include, but not be limited to:
 - a. The name and address of the reclamation contractor;
 - b. The name and address of the surface owner;
 - c. The location and name of the disposal site for the pit water; and,
 - d. A description of the proposed work, including details on treatment and disposition of the drilling waste.

All pit water must be removed prior to reclamation. Drilling waste should be encapsulated in the pit and covered with at least four feet [1.22 meters] of backfill and topsoil and surface sloped, when practicable, to promote surface drainage away from the reclaimed pit area.

History: Effective _____.

General Authority
NDCC 38-08-04

Law Implemented
NDCC 38-08-04

43-02-03-21. CASING, TUBING, AND CEMENTING REQUIREMENTS. All wells drilled for oil, natural gas or injection shall be completed with strings of casing which shall be properly cemented at sufficient depths to adequately protect and isolate all formations containing water, oil or gas or any combination of these; protect the pipe through salt sections encountered; and isolate the uppermost sand of the Dakota group.

Drilling of the surface hole shall be with freshwater-based drilling mud or other method approved by the director which will protect all freshwater-bearing strata. The surface casing shall consist of new or reconditioned pipe that has been previously tested to one thousand pounds per square inch [6900 kilopascals]. The surface casing shall be set and cemented at a point not less than fifty feet [15.24 meters] below the base of the Fox Hills formation. Sufficient cement shall be used on surface casing to fill the annular space behind the casing to the bottom of the cellar, if any, or to the surface of the ground. If the annulus space is not adequately filled with cement, the director shall be notified immediately. The operator shall diligently perform remedial work after obtaining approval from the director. All strings of surface casing shall stand cemented under pressure for at least twelve hours before drilling the plug or initiating tests. The term "under pressure" as used herein shall be complied with if one float valve is used or if pressure is otherwise held. Cementing shall be by the pump and plug method or other methods approved by the director. The director is authorized to require an accurate gauge be maintained on the surface casing of any well, not properly plugged and abandoned, to detect any buildup of pressure caused by the migration of fluids.

Surface casing strings must be allowed to stand under pressure until the tail cement has reached a compressive strength of at least five hundred pounds per square inch [3450 kilopascals]. All filler cements utilized must reach a compressive strength of at least two hundred fifty pounds per square inch [1725 kilopascals] within twenty-four hours and at least three hundred fifty pounds per square inch [2415 kilopascals] within seventy-two hours. All compressive strengths on surface casing cement shall be calculated at a temperature of eighty degrees Fahrenheit [26.67 degrees Celsius].

Production or intermediate casing strings shall consist of new or reconditioned pipe that has been previously tested to two thousand pounds per square inch [13800 kilopascals]. Such strings must be allowed to stand under pressure until the tail cement has reached a compressive strength of at least five hundred pounds per square inch [3450 kilopascals]. All filler cements utilized must reach a compressive strength of at least two hundred fifty pounds per square inch [1725 kilopascals] within twenty-four hours and at least five hundred pounds per square inch [3450 kilopascals] within seventy-two hours, although in any horizontal well performing a single stage cement job from a measured depth of greater than thirteen thousand feet [3962.4 meters], the filler cement utilized

must reach a compressive strength of at least two hundred fifty pounds per square inch [1725 kilopascals] within forty-eight hours and at least five hundred pounds per square inch [3450 kilopascals] within ninety-six hours. All compressive strengths on production or intermediate casing cement shall be calculated at a temperature found in the Mowry formation using a gradient of 1.2 degrees Fahrenheit per one hundred feet [30.48 meters] of depth plus eighty degrees Fahrenheit [26.67 degrees Celsius]. ~~After cementing, the casing shall be tested by application of pump pressure of at least one thousand five hundred pounds per square inch [10350 kilopascals]. If, at the end of thirty minutes, this pressure has dropped one hundred fifty pounds per square inch [1035 kilopascals] or more, the casing shall be repaired. Thereafter, the casing shall again be tested in the same manner. Further work shall not proceed until a satisfactory test has been obtained. The casing in a horizontal well may be tested by use of a mechanical tool set near the casing shoe after the horizontal section has been drilled.~~

After cementing, each casing string shall be tested by application of pump pressure of at least one thousand five hundred pounds per square inch [10350 kilopascals]. If, at the end of thirty minutes, this pressure has dropped one hundred fifty pounds per square inch [1035 kilopascals] or more, the casing shall be repaired after receiving approval from the director. Thereafter, the casing shall again be tested in the same manner. Further work shall not proceed until a satisfactory test has been obtained. The casing in a horizontal well may be tested by use of a mechanical tool set near the casing shoe after the horizontal section has been drilled.

All flowing wells must be equipped with tubing. A tubing packer must also be utilized unless a waiver is obtained after demonstrating the casing will not be subjected to excessive pressure or corrosion. The packer must be set as near the producing interval as practicable, but in all cases must be above the perforations.

History: Amended effective April 30, 1981; January 1, 1983; May 1, 1992; July 1, 1996; January 1, 1997; September 1, 2000; July 1, 2002; May 1, 2004; January 1, 2006; April 1, 2010.

General Authority
NDCC 38-08-04

Law Implemented
NDCC 38-08-04

43-02-03-25. DEVIATION TESTS AND DIRECTIONAL SURVEYS. When any well is drilled or deepened, tests to determine the deviation from the vertical shall be taken at least every one thousand feet [304.8 meters]. The director is authorized to waive the deviation test for a shallow gas well if the necessity therefor can be demonstrated to the director's satisfaction. When the deviation from the vertical exceeds five degrees at any point, the director may require that the hole be straightened. Directional surveys may be required by the director, whenever, in the director's judgment, the location of the bottom of the well is in doubt.

A directional survey shall be made and filed with the director on any well utilizing a whipstock or any method of deviating the well bore. The obligation to run the directional survey may be waived by the director when a well bore is deviated to sidetrack junk in the hole, straighten a crooked hole, control a blowout, or if the necessity therefor can be demonstrated to the director's satisfaction. The survey contractor shall file with the director free of charge one certified electronic copy of all surveys, in a form approved by the director, within thirty days of attaining total depth. Such survey shall be in reference to true north. The director may require the directional survey to

be filed immediately after completion if the survey is needed to conduct the operation of the director's office in a timely manner. Special permits may be obtained to drill directionally in a predetermined direction as provided above, from the director.

If the director denies a request for a permit to directionally drill, the director shall advise the applicant immediately of the reasons for denial. The decision of the director may be appealed to the commission.

History: Amended effective April 1, 1980; April 30, 1981; January 1, 1983; May 1, 1990; May 1, 1992; May 1, 1994; September 1, 2000; January 1, 2006; April 1, 2010.

General Authority
NDCC 38-08-04

Law Implemented
NDCC 38-08-04

Create a new Section of the Administrative Code:

43-02-03-27.1 HYDRAULIC FRACTURE STIMULATION.

1. For hydraulic fracture stimulation performed through a frac string run inside the intermediate casing string:
 - a. The frac string must be either stung into a liner or run with a packer set at a minimum depth of one hundred feet [30.48 meters] below the top of cement or one hundred feet [30.48 meters] below the top of the Inyan Kara formation whichever is deeper.
 - b. The intermediate casing-frac string annulus must be pressurized and monitored during frac operations.
 - c. An adequately sized, function tested pressure relief valve must be utilized on the treating lines from the pumps to the wellhead, with suitable check valves to limit the volume of flowback fluid should the relief valve open. The relief valve must be set to limit line pressure to no more than eighty-five percent of the internal yield pressure of the frac string.
 - d. An adequately sized, function tested pressure relief valve and an adequately sized diversion line must be utilized to divert flow from the intermediate casing to a pit or containment vessel in case of frac string failure. The relief valve must be set to limit annular pressure to no more than eighty-five percent of the lowest internal yield pressure of the intermediate casing string.
 - e. The surface casing valve must be fully open and connected to a diversion line rigged to a pit or containment vessel.
 - f. An adequately sized, function tested remote operated frac valve must be utilized between the treating line and the wellhead.

- (21)

- g. The surface casing valve must be fully open and connected to a diversion line rigged to a pit or containment vessel.
 - h. An adequately sized, function tested remote operated frac valve must be utilized between the treating line and the wellhead.
 - i. Within sixty days after the hydraulic fracture stimulation is performed, the owner, operator, or service company shall post on the FracFocus Chemical Disclosure Registry all elements made viewable by the FracFocus website.
3. If during the stimulation, the pressure in the intermediate casing-surface casing annulus exceeds three hundred fifty pounds per square inch [2413 kilopascals] gauge, the owner or operator shall verbally notify the director as soon as practicable but no later than twenty-four hours following the incident.

History: Effective _____

General Authority
NDCC 38-08-04

Law Implemented
NDCC 38-08-04

43-02-03-28. SAFETY REGULATION. During drilling operations all oil wells shall be cleaned into a pit or tank, not less than forty feet [12.19 meters] from the derrick floor and one hundred fifty feet [45.72 meters] from any fire hazard.

All flowing oil wells must be produced through an approved oil and gas separator or emulsion treater of ample capacity and in good working order. No boiler, portable electric lighting generator, or treater shall be placed nearer than one hundred fifty feet [45.72 meters] to any producing well or oil tank. Placement as close as one hundred twenty-five feet [38.10 meters] may be allowed if a flame arrestor is utilized on the equipment. Any rubbish or debris that might constitute a fire hazard shall be removed to a distance of at least one hundred fifty feet [45.72 meters] from the vicinity of wells and tanks. All waste shall be burned or disposed of in such manner as to avoid creating a fire hazard. All vegetation must be removed to a safe distance from any production equipment to eliminate a fire hazard.

The director may require remote operated or automatic shut-down equipment to be installed on, or shut in for no more than forty days, any well that is likely to cause a serious threat of pollution or injury to the public health or safety.

No well shall be drilled nor production or injection equipment installed less than five hundred feet [152.40 meters] from an occupied dwelling unless agreed to in writing by the ~~surface~~ owner of the dwelling or authorized by order of the commission.

Subsurface pressure must be controlled during all drilling, completion, and well-servicing operations with appropriate fluid weight and pressure control equipment.

History: Amended effective January 1, 1983; May 1, 1990; September 1, 2000; January 1, 2006; January 1, 2008.

General Authority
NDCC 38-08-04

Law Implemented
NDCC 38-08-04

Create a new Section of the Administrative Code:

43-02-03-30.1. LEAK AND SPILL CLEANUP. At no time shall any spill or leak be allowed to flow over, pool, or rest on the surface of the land or infiltrate the soil. Discharged fluids must be properly removed and may not be allowed to remain standing within or outside of diked areas, although the remediation of such fluids may be allowed on-site if approved by the director. Operators must respond with appropriate resources to contain and clean up spills.

History: Effective _____

General Authority
NDCC 38-08-04

Law Implemented
NDCC 38-08-04

43-02-03-31. WELL LOG, COMPLETION, AND WORKOVER REPORTS. After the plugging of a well, a plugging record (form 7) shall be filed with the director. After the completion of a well, recompletion of a well in a different pool, or drilling horizontally in an existing pool, a completion report (form 6) shall be filed with the director. In no case shall oil or gas be transported from the lease prior to the filing of a completion report unless approved by the director. The operator shall cause to be run an open hole electrical, radioactivity, or other similar log, or combination of open hole logs, of the operator's choice, from which formation tops and porosity zones can be determined. The operator shall cause to be run a gamma ray log from total depth to ground level elevation of the well bore. ~~The~~ Prior to completing the well, the operator shall cause to be run a log from which the presence and quality of bonding of cement can be determined in every well in which production or intermediate casing has been set. The obligation to log may be waived or postponed by the director if the necessity therefor can be demonstrated to the director's satisfaction. Waiver will be contingent upon such terms and conditions as the director deems appropriate. All logs run shall be available to the director at the well site prior to proceeding with plugging or completion operations. ~~Two copies of all~~ All logs run shall be submitted to the director free of charge. Logs shall be submitted as one ~~paper~~ digital TIFF (Tagged Image File Format) copy and one digital LAS (~~log~~ Log ASCII) formatted copy, or a format approved by the director. In addition, operators shall file two copies of drill stem test reports and charts, formation water analyses, core analyses, geologic reports, and noninterpretive lithologic logs or sample descriptions if compiled by the operator.

All information furnished to the director on new permits, except the operator name, well name, location, spacing or drilling unit description, spud date, rig contractor, central tank battery number, and any production runs, shall be kept confidential for not more than six months if

requested by the operator in writing. The six-month period shall commence on the date the well is completed or the date the written request is received, whichever is earlier. If the written request accompanies the application for permit to drill or is filed after permitting but prior to spudding, the six-month period shall commence on the date the well is spudded. The director may release such confidential completion and production data to health care professionals, emergency responders, and state, federal, or tribal environmental and public health regulators if the director deems it necessary to protect the public's health, safety, and welfare.

All information furnished to the director on recompletions or reentries, except the operator name, well name, location, spacing or drilling unit description, spud date, rig contractor, and any production runs, shall be kept confidential for not more than six months if requested by the operator in writing. The six-month period shall commence on the date the well is completed or the date the well was approved for recompletion or reentry, whichever is earlier. Any information furnished to the director prior to approval of the recompletion or reentry shall remain public.

Approval must be obtained on a sundry notice (form 4) from the director prior to perforating or recompleting a well in a pool other than the pool in which the well is currently permitted.

After the completion of any remedial work, or attempted remedial work such as plugging back or drilling deeper, acidizing, shooting, formation fracturing, squeezing operations, setting liner, perforating, reperforating, or other similar operations not specifically covered herein, a report on the operation shall be filed on a sundry notice (form 4) with the director. The report shall present a detailed account of all work done and the date of such work; the daily production of oil, gas, and water both prior to and after the operation; the shots per foot, size, and depth of perforations; the quantity of sand, crude, chemical, or other materials employed in the operation; and any other pertinent information or operations which affect the original status of the well and are not specifically covered herein.

Upon the installation of pumping equipment on a flowing well, or change in type of pumping equipment designed to increase productivity in a well, the operator shall submit a sundry notice (form 4) of such installation. The notice shall include all pertinent information on the pump and the operation thereof including the date of such installation, and the daily production of the well prior to and after the pump has been installed.

All forms, reports, logs, and other information required by this section shall be submitted within thirty days after the completion of such work, although a completion report shall be filed immediately after the completion or recompletion of a well in a pool or reservoir not then covered by an order of the commission.

History: Amended effective April 30, 1981; January 1, 1983; May 1, 1990; May 1, 1992; May 1, 1994; July 1, 1996; September 1, 2000; July 1, 2002; January 1, 2006; January 1, 2008; April 1, 2010.

General Authority
NDCC 38-08-04

Law Implemented
NDCC 38-08-04

Create a new Section of the Administrative Code:**43-02-03-34.1. RECLAMATION OF SURFACE.**

1. Within a reasonable time, but not more than one year, after a well is plugged, or if a permit expires, has been cancelled or revoked, the well site, access road, and other associated facilities constructed for the well shall be reclaimed as closely as practicable to original condition. Prior to site reclamation, the operator or the operator's agent shall file a sundry notice (form 4) with the director and obtain approval of a reclamation plan. The operator or operator's agent shall provide a copy of the proposed reclamation plan to the surface owner at least ten days prior to commencing the work unless waived by the surface owner. Verbal approval to reclaim the site may be given. The notice shall include, but not be limited to:
 - a. The name and address of the reclamation contractor;
 - b. The name and address of the surface owner and the date when a copy of the proposed reclamation plan was provided to the surface owner;
 - c. A description of the proposed work, including topsoil redistribution and reclamation plans for the access road and other associated facilities; and
 - d. Reseeding plans, if applicable.

The commission will mail a copy of the approved notice to the surface owner.

All equipment, waste and debris shall be removed from the site. Flow lines shall be purged in a manner approved by the director. Flow lines shall be removed if buried less than three feet [91.44 centimeters] below final contour.

2. Gravel or other surfacing material shall be removed, stabilized soil shall be remediated, and the well site, access road, and other associated facilities constructed for the well shall be reshaped as near as is practicable to original contour.
3. The stockpiled topsoil shall be evenly distributed over the disturbed area, and where applicable the area revegetated with native species or according to the reasonable specifications of the appropriate government land manager or surface owner.
4. Within thirty days after completing any reclamation, the operator shall file a sundry notice with the director reporting the work performed.

5. The director, with the consent of the appropriate government land manager or surface owner, may waive the requirement of reclamation of the site and access road after a well is plugged.

History: Effective _____

General Authority
NDCC 38-08-04

Law Implemented
NDCC 38-08-04

43-02-03-49. OIL SPILLS, PRODUCTION EQUIPMENT, DIKES, AND SEALS.

Storage of oil in underground or partially buried tanks or containers is prohibited. Surface oil tanks and production equipment must be devoid of leaks and in good condition. ~~Unusable~~ Unused tanks and production equipment must be removed from the site or ~~repaired and~~ placed into service, within a reasonable time period, not to exceed one year. Dikes must be erected and maintained around oil tanks at any production facility built or rebuilt on or after July 1, 2000.

Dikes must be erected around oil tanks at any new production facility within thirty days after the well has been completed. Dikes must be erected and maintained around oil tanks at production facilities built prior to July 1, 2000, when deemed necessary by the director. Dikes as well as the base material under the dikes and within the diked area must be constructed of sufficiently impermeable material to provide emergency containment. Dikes must be of sufficient dimension to contain the total capacity of the largest tank plus one day's fluid production. The required capacity of the dike may be lowered by the director if the necessity therefor can be demonstrated to the director's satisfaction.

~~At no time shall oil be allowed to flow over or pool on the surface of the land or infiltrate the soil. Discharged oil must be properly removed and may not be allowed to remain standing within or outside of any diked areas.~~

Numbered metal security seals shall be properly utilized on all oil access valves and access points to secure the tank or battery of tanks.

History: Amended effective April 30, 1981; January 1, 1983; May 1, 1992; September 1, 2000; July 1, 2002; May 1, 2004; April 1, 2010.

General Authority
NDCC 38-08-04

Law Implemented
NDCC 38-08-04

43-02-03-51. TREATING PLANT. Before construction of a treating plant and upon written application for a treating plant permit stating in detail the location, type, capacity of the plant contemplated, method of processing proposed, and the plan of operation for all plant waste, the commission shall set such application for hearing to determine whether the proposed plant and method of processing will actually and efficiently process, treat, and reclaim tank bottom emulsion and other waste oils, and whether there is need for such a plant. The operator of any portable treating plant shall notify the director as to all changes in location of said plant. No treating plant

shall operate except by order of the commission. The disposition of all products and waste must be reported monthly on form 5p. Upon approval of a treating plant and before construction begins, the permittee shall file with the commission a surety bond or cash bond conditioned upon compliance with all laws, rules and regulations, and orders of the commission. The bond amount shall be specified in the commission order authorizing the treating plant and shall be based upon the location, type, and capacity of the plant, processing method, and plan of operation for all plant waste approved in the commission order and shall be payable to the industrial commission of North Dakota. In no case shall the bond amount be set lower than ~~twenty-five~~ fifty thousand dollars.

History: Amended effective January 1, 1983; May 1, 1990; May 1, 1992; September 1, 2000.

General Authority
NDCC 38-08-04

Law Implemented
NDCC 38-08-04

43-02-03-53. SALTWATER HANDLING FACILITIES.

1. All saltwater liquids or brines produced with oil and natural gas shall be processed, stored, and disposed of without pollution of freshwater supplies. ~~At no time shall saltwater liquids or brines be allowed to flow over or pool on the surface of the land or infiltrate the soil.~~
2. Underground injection of saltwater liquids and brines shall be in accordance with chapter 43-02-05.
3. Surface facilities are acceptable provided that:
 - a. They are devoid of leaks and constructed of materials resistant to the effects of produced saltwater liquids, brines, or chemicals that may be contained therein. The above materials requirement may be waived by the director for tanks presently in service and in good condition. ~~Unusable~~ Unused tanks and injection equipment must be removed from the site or ~~repaired and~~ placed into service, within a reasonable time period, not to exceed one year.
 - b. Dikes must be erected and maintained around saltwater tanks at any saltwater handling facility built or rebuilt on or after July 1, 2000. Dikes must be erected around saltwater tanks at any new facility within thirty days after the well has been completed. Dikes must be erected and maintained around saltwater tanks at saltwater handling facilities built prior to July 1, 2000, when deemed necessary by the director. Dikes as well as the base material under the dikes and within the diked area must be constructed of sufficiently impermeable material to provide emergency containment. Dikes must be of sufficient dimension to contain the total capacity of the largest tank plus one day's fluid production. The required capacity of the dike may be lowered by the director if the necessity therefor can be demonstrated to the director's satisfaction. Discharged saltwater liquids or brines must be properly removed and may not be allowed to remain standing within or outside of any diked areas.

4. The operator shall take steps to minimize the amount of solids stored at the facility.
5. Any salable crude oil recovered from a saltwater handling facility shall be reported on a form 5 SWD.

History: Amended effective April 30, 1981; January 1, 1983; May 1, 1992; September 1, 2000; July 1, 2002; May 1, 2004; April 1, 2010.

General Authority
NDCC 38-08-04

Law Implemented
NDCC 38-08-04

43-02-03-54. INVESTIGATIVE POWERS. Upon receipt of a written complaint from any surface owner or lessee, royalty owner, mineral owner, local, state, or federal official, ~~or any other interested party~~, alleging a violation of the oil and gas conservation statutes or any rule, regulation, or order of the commission, the director shall ~~immediately cause an investigation of such complaint to be made~~ within a reasonable time reply in writing to the person who submitted the complaint stating that an investigation of such complaint will be made or the reason such investigation will not be made. The person who submitted the complaint may appeal the decision of the director to the commission. The director may also conduct such investigations on the director's own initiative or at the direction of the commission. If, after such investigation, the director affirms that cause for complaint exists, the director shall report the results of the investigation to the person who submitted the complaint, if any, to the person who was the subject of the complaint and to the commission. The commission shall institute such legal proceedings as, in its discretion, it believes are necessary to enjoin further violations.

History: Amended effective April 30, 1981; January 1, 1983; May 1, 1992.

General Authority
NDCC 38-08-04
38-08-12

Law Implemented
NDCC 38-08-04
38-08-12

43-02-03-55. ABANDONMENT OF WELLS - SUSPENSION OF DRILLING.

1. The removal of production equipment or the failure to produce oil or gas, ~~other than a gas well shut in for lack of a market~~, or the removal of production equipment or the failure to produce water from a source well, for one year constitutes abandonment of the well. The removal of injection equipment or the failure to use an injection well for one year constitutes abandonment of the well. The failure to plug a stratigraphic test hole within one year of reaching total depth constitutes abandonment of the well. An abandoned well must be plugged and its site must be reclaimed pursuant to sections 43-02-03-34 and 43-02-03-~~19~~34.1.
2. The director may waive for one year the requirement to plug and reclaim an abandoned well by giving the well temporarily abandoned status. This status may only be given to wells that are to be used for purposes related to the production of oil and gas. If a well is given temporarily abandoned status, the well's perforations must be isolated, the

integrity of its casing must be proven, and its casing must be sealed at the surface, all in a manner approved by the director. The director may extend a well's temporarily abandoned status beyond one year. A fee of one hundred dollars shall be submitted for each application to extend the temporary abandonment status of any well.

3. In addition to the waiver in subsection 2, the director may also waive the duty to plug and reclaim an abandoned well for any other good cause found by the director. If the director exercises this discretion, the director shall set a date or circumstance upon which the waiver expires.
4. The director may approve suspension of the drilling of a well. If suspension is approved, a plug must be placed at the top of the casing to prevent any foreign matter from getting into the well. When drilling has been suspended for thirty days, the well, unless otherwise authorized by the director, must be plugged and its site reclaimed pursuant to sections 43-02-03-34 and 43-02-03-~~19~~34.1.

History: Amended effective April 30, 1981; January 1, 1983; May 1, 1990; May 1, 1992; August 1, 1999; January 1, 2008; April 1, 2010.

General Authority
NDCC 38-08-04

Law Implemented
NDCC 38-08-04

43-02-03-88.1. SPECIAL PROCEDURES FOR INCREASED DENSITY WELLS, POOLING, FLARING EXEMPTION, UNDERGROUND INJECTION, COMMINGLING, CONVERTING MINERAL WELLS TO FRESHWATER WELLS, AND CENTRAL TANK BATTERY OR CENTRAL PRODUCTION FACILITIES APPLICATIONS.

1. Applications to amend field rules to allow additional wells on existing spacing units, for pooling under North Dakota Century Code section 38-08-08, for a flaring exemption under North Dakota Century Code section 38-08-06.4 and section 43-02-03-60.2, for underground injection under chapter 43-02-05, for commingling in one well bore the fluids from two or more pools under section 43-02-03-42, for converting a mineral well to a freshwater well under section 43-02-03-35, and for establishing central tank batteries or central production facilities under section 43-02-03-48.1, must be signed by the applicant or the applicant's representative. The application must contain or refer to attachments that contain all the information required by law as well as the information the applicant wants the commission to consider in deciding whether to grant the application. The application must designate an employee or representative of the applicant to whom the commission can direct inquiries regarding the application.
2. The applications referred to in subsection 1 will be advertised and scheduled for hearing as are all other applications received by the commission. The applicant, however, unless required by the director, need not appear at the hearing scheduled to consider the application, although additional evidence may be submitted prior to the hearing. Any interested party may appear at the hearing to oppose or comment on the application.

Any interested party may also submit written comments on or objections to the application no later than five p.m. on the last business day prior to the hearing date. Such submissions may be part of the record in the case if allowed by the hearing examiner.

3. The director is authorized, on behalf of the commission, to grant or deny the applications referred to in subsection 1.
4. In any proceeding under this section, the applicant, at the hearing, may supplement the record by offering testimony and exhibits in support of the application.
5. In the event the applicant is not required by the director to appear at the hearing and an interested party does appear to oppose the application or submits a written objection to the application, the hearing officer shall continue the hearing to a later date, keep the record open for the submission of additional evidence, or take any other action necessary to ensure that the applicant, who does not appear at the hearing as the result of subsection 2, is accorded due process.

History: Effective May 1, 1992; amended effective May 1, 1994; May 1, 2004.

General Authority
NDCC 38-08-04
38-08-11

Law Implemented
NDCC 38-08-04
38-08-08

43-02-03-90.2. OFFICIAL NOTICE RECORD. The evidence in each case heard by the commission, unless specifically excluded by the hearing officer, includes the certified directional surveys, and all oil, water, and gas production records on file with the commission.

Any interested party may submit written comments on or objections to the application prior to the hearing date. Such submissions must be received no later than five p.m. on the last business day prior to the hearing date and may be part of the record in the case if allowed by the hearing examiner.

History: Effective May 1, 1992; April 1, 2010.

General Authority
NDCC 28-32-06

Law Implemented
NDCC 28-32-06

GEOPHYSICAL EXPLORATION REQUIREMENTS CHAPTER 43-02-12

43-02-12-06. NOTIFICATION OF WORK PERFORMED. The director may require progress reports prior to the completion of a project. Within thirty days following the completion of geophysical exploration by any person within this state, such person shall file with the commission a seismic completion report in the form of an affidavit deposing that the seismic project was

completed in accordance with chapter 43-02-12, and incorporating a postplot map displaying the actual source point location and the location of all undetonated (loaded) holes, blowouts, and flowing holes or any other problem holes the director deems necessary. If obtained by the contractor, the latitude and longitude of each source and receiver point shall be submitted to the commission to the nearest tenth of a second.

Any person plugging a seismic hole must submit a plugging report and an affidavit of plugging detailing the line number, shot point number, hole depth, drill type, hole condition (wet, dry), bentonite used (sacks, capsules), and the depth at which the surface plug was set, and all other information necessary to describe the conditions of the shot hole.

The director is authorized to approve an operator's request to suspend a geophysical exploration project, although no suspension shall be granted beyond ninety days unless all charges are detonated.

The director is authorized to suspend operations of the entire geophysical exploration project, or any portion thereof, if further activity will cause excessive damage to the surface of the land. The geophysical exploration activity may continue upon the director approving a plan to mitigate the damage.

History: Effective December 1, 1997; amended effective September 1, 2000; May 1, 2004; January 1, 2008; April 1, 2010.

General Authority
NDCC 38-08.1

Law Implemented
NDCC 38-08.1-02,
38-08.1-05